



TECHNICAL DATA

Product Name: **SEAL WHITE**

Specification: ACRYLIC LATEX Modified, General Waterproofing Chemical with Additional power of Heat Reflection

NXT's **SEAL WHITE** is an elastomeric Heat/Waterproofing coating specially designed for roof, Walls & Water tanks waterproofing etc. NXT's **SEAL WHITE** is suitable for use on all types of structures in industrial, commercial and residential areas including those situated in coastal environments.

NXT's **SEAL WHITE** is a two part acrylic latex polymer modified coating. It is supplied in a pre packaged form. This product is designed to be mixed easily on site using a slow speed drill fitted with a mixing paddle and then applied to the substrate using a brush, roller, trowel or spray. The finished coating is of a slightly granular texture.

Field of Application: NXT's **SEAL WHITE** can be used on concrete, brick and block work, It is equally suited for both new and existing structures and provides a durable, flexible waterproof coating suitable in accepting light foot traffic.

Touch dry: 20 Minutes
Drying Time: 2 Hours
Pot Life: 2 Hours

Thinner: Soft drinking water

Dilution: According to desire and viscosity depending on the surface and tools

Method of Application: Brush, Roller, sprayer

Surface Preparation: Clean down thoroughly to remove all dirt, dust and loose material. Ensure surface is free from oil, grease, mould and release agents.

Tools Cleaning: For well clean, wash with soft water.

Storage: Store at room temperature between 20 °C to 40 °C

Shelf Life: One Year in original sealed container

Precautions: Material should be mix thoroughly before use, keep out of reach of children.

Limitations: Do not apply at temperatures below 10°C or when it is liable to drop below 10°C during the drying period.

Head Office: Fatima Plaza, Office # 2, 1st Floor I-10 Markaz Islamabad.
Ph:92-51-4436802